

SOKKIA

B20 · B30A · B40A

AUTO LEVEL



Durable, Dependable, High Value Auto Levels

- 3 Models - 32x, 28x, and 24x Magnifications
- Rapid, Accurate, and Stable Automatic Compensation
- Ultra-Short 20cm (7.9 in.) Focusing
- All-Weather Dependability
- Clampless, Endless Fine Horizontal Adjustments

B20

High-precision model



Magnification
32x

Objective Aperture
42mm

Accuracy
0.7mm

Minimum Focus
20cm

Protection
IPX6

Weight
1.85kg

B30A

Versatile model for surveying,
engineering and construction



Magnification
28x

Objective Aperture
36mm

Accuracy
1.5mm

Minimum Focus
20cm

Protection
IPX6

Weight
1.5kg

B40A

Economical model for
engineering and construction



Magnification
24x

Objective Aperture
32mm

Accuracy
2.0mm

Minimum Focus
20cm

Protection
IPX6


Weight
1.5kg

B2o · B30A · B40A

SPECIFICATIONS

Rapid, Stable, and Durable Compensator

The compensator of B20/B30A/B40A incorporates four suspension wires made of super-high-tensile metal that features minimal thermal expansion coefficient, providing unmatched durability and accuracy. Finely tuned magnetic damping system quickly levels and stabilizes the line of sight despite the fine vibrations present when working near heavy equipment or busy roadways.



20cm (7.9 in.) - Ultra-Short Minimum Focus

B20/B30A/B40A can focus on objects at 20cm (7.9 in.) in front of the telescope. This feature dramatically facilitates the works in confined spaces.

Horizontal Circle for Angle Measurement

Horizontal angles can be directly read in 1° or 1gon units. Free rotation feature allows you to read any angle from zero.



All-Weather Dependability

With the IPX6 rating, the instrument is protected against powerful water jets from all directions, meaning B20/B30A/B40A withstands a sudden shower or torrential rainfall.

The advanced protection design also deters clouding or condensation inside the telescope.

	B2o	B30A	B40A
Telescope			
Length	215mm (8.46in.)	214mm (8.42in.)	
Magnification	32x	28x	24x
Objective Aperture	42mm (1.65 in.)	36mm (1.42 in.)	32mm (1.26 in.)
Resolving Power	3"	3.5"	4"
Field of View (at 100m/328ft.)	1°20' (2.3m / 7.5ft.)	1°25' (2.5m / 8.2ft.)	
Minimum Focus	0.2m (7.9 in.) from end of telescope 0.3m (1ft.) from instrument center		
Image			
Stadia Constant	Erect		
Stadia Ratio	0		
Focusing Knob	2-speed	1-speed	
Sighting Aid	Peep Sight		Gun Sight
Accuracy (1km double run leveling)			
Without Micrometer	0.7mm (0.03 in.)	1.5mm (0.06 in.)	2.0mm (0.08 in.)
With Micrometer	0.5mm (0.02 in.)	n/a	
Compensator			
Type	Pendulum compensator with magnetic damping system		
Setting Accuracy	0.3"	0.5"	
Working Range	±15'		
Circular Level			
Sensitivity	10' / 2mm		
Horizontal Circle			
Diameter	103mm (4.1in.)	99mm (3.9in.)	
Minimum Division	1° / 1gon		
General			
Water Resistance	IPX6 (IEC 60529:2001)		
Operating Temperature	-20 to +50°C (-4 to +122°F)		
Size	Width	130mm (5.12in.)	122mm (4.8in.)
	Length	215mm (8.46in.)	214mm (8.4in.)
	Height	140mm (5.51in.)	
Weight	1.85kg (4.1lbs.)	1.5kg (3.3lbs.)	

Standard Package/ Optional Accessories



- Main unit
- Hex wrench
- Adjusting pins
- Vinyl cover (B20/B30A)
- Plumb bob (B20/B30A)
- Cleaning cloth
- Lens cap
- User manual
- Hard carrying case



Diagonal Eyepiece DE16 (B20)



Optical Micrometer OM5 (B20)



40x Eyepiece EL5 (B20)

SOKKIA QUALITY Ultimate Environmental Performance and Durability

SOKKIA has been performing environmental tests against a set of expected job site conditions to certify the products for the long term use. The B Series has been tested by the special inspection equipment for complete waterproofness. The B Series also has the highest environmental performance and durability in SOKKIA's Auto Level history, proven by tests against temperature, humidity, vibration and drop.



Water Proof Test (IPX6)

The B Series is proven to withstand powerful water jets from all directions without any submergence inside the unit



Cold and Heat Resistance Test

The B Series has passed operating temperature tests from -20°C to +50°C degree.



Durability Test

The B Series has passed strict durability tests including rotation of leveling foot screw, Focusing knob and Horizontal fine motor screw.



TOPCON CORPORATION

75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan
www.topcon.co.jp

<Contact to>

Sokkia Singapore Positioning Sales Pte. Ltd.

1 Jalan Kilang Timor, #09-01 Pacific Tech Centre, Singapore 159303
Phone: (+65)6479-3966 Fax: (+65)6479-4966
Email: sales@sokkia.com.sg
Web: www.sokkia.com.sg/

©2016 Topcon Corporation All rights reserved. SSP

- Specifications may vary by region and are subject to change without notice.

- Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.

- Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license.

- Other trademarks and trade names are those of their respective owners.

Your local Authorized Dealer is: